

MOTORS		Motor speed 50 Hz												Motor speed 60 Hz					
		8 poles			6 poles			4 poles			2 poles			6 poles			4 poles		
		750 R.P.M.			1000 R.P.M.			1500 R.P.M.			3000 R.P.M.			1200 R.P.M.			1800 R.P.M.		
TYPE	Ø SHAFT	kW	HP	Coupling	kW	HP	Coupling	kW	HP	Coupling	kW	HP	Coupling	kW	HP	Coupling	kW	HP	Coupling
71	14				0,25	0,33	10	0,25	0,33	10	0,37	0,5	10	0,25	0,35	10	0,25	0,35	10
80	19				0,37	0,5		0,37	0,5		0,55	0,75		0,75	1		0,55	0,75	
90S	24				0,55	0,75	20	0,75	1	20	1,1	1,5	20	1,1	1,5	20	1,1	1,5	20
90L	24	0,55	0,75	20	1,1	1,5		1,5	2		2,2	3		2,2	3		1,5	2	
100L	28	1,1	1,5	30	1,5	2	30	2,2	3	30	3	4	30	3	4	30	3	4	30
112M	28	1,5	2		2,2	3		3	4		4	5,5		4	5,5		4	5,5	
132	38	-	-	30P	3	4	30P	5,5	7,5	30P	5,5	7,5	30P	7,5	10	30P	7,5	10	30P
132M	38	3	4	40P	4	5,5		7,5	10		-	-		7,5	10		5,5	7,5	
160M	42	4	5,5	50	7,5	10	40P	11	15	30P	11	15	30P	11	15	30P	11	15	30P
160L	42	7,5	10	55	11	15		15	20		18,5	25		15	20		18,5	25	
180M	48	-	-		-	-	50	18,5	25	40P	22	30	30	22	30	30P	22	30	30P
180L	48	11	15	60	15	20		22	30		-	-		30	40		15	20	
200L	55	15	20	60	18,5	25	55	30	40	50	30	40	50	30	40	50	30	40	40P
225S	60	18,5	25	65	22	30		37	50		37	50		37	50		37	50	
225M	55	-	-		30	40	60	-	-	55	45	60	30P	-	-	55	-	-	50
250M	60	-	-	65	-	-		-	-		55	75		-	-		55	75	
280S	65	-	-		37	50	65	75	100	60	75	100	50	75	100	65	75	100	55
280M	75	45	60	70P	45	60		75	100		90	125		45	60		90	125	
315S	65	-	-		-	-	70P	-	-	65	110	150	50	110	150	65	110	150	60
	80	55	75	75P	75	100		110	150		132	180		110	150		132	180	
315M	65	-	-		-	-	75P	-	-	70P	132	180	55	132	180	70P	132	180	65
	75	100		80P	90	125		132	180		160	220		90	125		160	220	
	80	-	-		110	150	80P	110	150	75P	160	220	70P	160	220	75P	160	220	70P
	90	125		132	180	200		270	200		270	250		340	250		340	250	
355S	80	-	-		-	-	80P	-	-	75P	-	-	75P	-	-	75P	-	-	75P
	100	132	180	85P	160	220		250	340		-	-		160	220		250	340	
355M	80	-	-		-	-	85P	-	-	75P	-	-	75P	-	-	75P	-	-	75P
	100	160	220	90P	200	270		200	270		315	430		200	270		315	430	
NON STANDARD MOTORS		330	450	90P	370	500	85P	510	700	80P				310	420	80P	440	600	75P
		600	800	95P	600	800	90P	810	1100	85P				440	600	85P	700	950	80P
		1000	1360	1200	1000	1360	95P	1300	1740	90P				800	1100	90P	1000	1360	85P
		1550	2100	1200/2	2000	2720	1200	2300	3100	95P				1380	1880	95P			
					3200	4350	1200/2	3850	5250	1200				2580	3500	1200			
													4200	5710	1200/2				

- For Couplings at 3000rpm, special balancing required.
- Slip curves with Couplings efficiency are available on request.